

NEW

COMPACT MULTIMEDIA AMPLIFIER

LA-1600AMP

1600W

2 CH

2 Ω
4 Ω
8 Ω

CLASS D



DESCRIPTION

This power amplifier is available in 1600W, with 2 channels.

Standard operation in low impedance: 2 / 4 / 8 Ω.
Operates on AC 220–240V mains supply.

Suitable for installations such as restaurants, boutiques, shops, hotels, etc

FEATURES

It is equipped with :

- 2 combo MIC inputs: Speakon / 6.35 mm JACK (balanced)
- 2 XLR MIC inputs (balanced)
- DIP switch settings for output mode (low-pass filter 30Hz / 50Hz)
- 2 Speakon outputs (CH1 / CH2)
- Independent volume control per input
- Thermal, overload and short-circuit protection



SPECIFICATIONS

LA-1600AMP

Type	Power amplifier
Power Supply	AC 220-240V
Output Power	8 Ω Stereo : 2 x 280W 4 Ω Stereo : 2 x 500W 2 Ω Stereo : 2 x 800W 8 Ω Bridge mono : 1000W 4 Ω Bridge mono : 1600W
Speaker Outputs	2-4-8 Ω
Frequency Response	20Hz - 20 000 Hz (± 3 dB)
Total Harmonic Distortion	< 0.5%
Signal-to-Noise Ratio	> 100 dB
Cooling	Fan
Power Consumption	200W
Protections	Thermal, overload, short-circuit
Dimensions (W x D x H)	483 x 306 x 89 mm - 2U
Weight	4.5 kg

MODEL DESIGNATION

Power amplifier 1600W. LA-1600AMP
(code 02784)