

ĀN PLĪGĪĒRŠĀ PĒRĒĀN PLĪGĪĒRŠ

# AMM-150-2



## DESCRIPTION

Amplificateur mural Classe D, 150 W.

It offers 70 V, 100 V and 4 Ω (low impedance) loudspeaker outputs.

It operates on a 115 V - 230 V - 50 / 60 Hz mains supply.

Use for typical installations such as chain shops, small hotels, etc.

## SPECIFICATIONS

It is equipped with :

- 1 USB/SD drive
- 1 Bluetooth receiver module for broadcasting from your mobile phone, tablet or laptop
- 2 switchable MIC/LINE/fantom inputs, including input 1 with Talk Over.
- 1 AUX input (RCA) and 1 AUX mini 3.5" jack input
- 1 Line Out (RCA)
- 15 V phantom power supply
- Individual volume control for each input, MASTER volume control
- HP 70 V, 100 V and 4 and 16 Ω outputs on screw terminal block
- Thermal, overload and short-circuit protection
- Output level meter
- Supplied with wall bracket for simple fixing
- 1 Wall-mounted box with key
- 1 wireless microphone
- 1 antenna for speaker microphone
- 1 hand-held microphone with HF antenna,
- 1 remote control
- 1x 8 GB SD card

## SPECIFICATIONS

	AMM-150-2
Type	Wall-mounted amplifier
Power supply	AC 115 V/230 V - 50/60 Hz
Output power	150 W RMS
Speaker outputs	4 Ω - 70 V - 100 V
Inputs/Sensitivity	MIC : -40 dBV AUX : -10 dBV LINE : -10 dB
Frequency band	MIC/LINE : 80 Hz - 20 000 Hz (± 3 dB) Input 4/TEL : 50 Hz - 18 000 Hz (± 3 dB)
Signal-to-noise ratio	MIC : > 70 dB AUX/LINE : > 80 dB
Total harmonic distortion	< 1 %
Tone settings	Bass : ± 10 dB à 100 Hz Treble : ± 10 dB à 10 000 Hz
Phantom power supply	15 V
Protection	Thermal, overload and short-circuit protection
Consumption	120 W
Other	Line Out : 0.5 V
Dimensions (W x D x H)	265 x 102 x 267 mm
Weight	3,5 kg

## MODEL DESIGNATION

150 W wall-mounted amplifier with cabinet ..... AMM-150-2  
(code 02370)