

### DESCRIPTION

Pair of 2-way 2 x 20 W flush-mount ceiling loudspeakers with active and passive drivers and Bluetooth receiver for use in any public space to create an atmospheric PA system.

Ideally suited to facilities such as shops, restaurants and nursing homes...

Auxiliary input via terminals.

### **BLUETOOTH SPEAKER**

Bluetooth technology enables a wireless connection to be established between audio sources such as smartphones, tablets, PCs, Android or Apple devices.

Automatic recognition of Bluetooth devices already paired are recognised. The range, depending on conditions of use, is up to 10 m.

### **ACOUSTIC QUALITY**

The high-quality loudspeaker reproduces a very natural sound, guaranteeing a uniform sound field.

The power of these 2 loudspeakers makes them ideal for use in areas of up to 100 m2.

## ASSEMBLY

Quick and easy to install, flat magnetic metal grille with ABS surround.

Discreet integration into the ceiling.


Private power supply and speaker cable included (5 m).

The active and passive loudspeakers are connected by terminals and form a stereo pair.

Only works in pairs.







SPECIFICATIONS	BS-C230
Туре	Pair of 2-way ceiling speakers
Material	Flat magnetic metal grille
Loudspeaker	12 cm + tweeter
Sound pressure	86 dB / 1 W / 1 m
Frequency band	100 - 20 000 Hz
Open angle	180 °
Open surface	At 4 or 5 m high: 65 to 100 m²
Power	20 W + 20 W
Impédance	8 N
Connection	On wire
Power supply	AC 230 V - 50/60 Hz
Dimensions (Ø x h)	Ø 214 x 88,9 mm
Weight per speaker	0,90 kg
Built-in diameter	0 172 mm

# MODEL DESIGNATION

2 x 20 W Bluetooth ceiling speakers	BS-C230
	(cude US3U3)

