

NEW

MICROPHONE STANDS

CS-041R CS-042R



MICROPHONE WITH
INTEGRATED SPEAKERS



VOTE



VIDEO
TRACKING



RECORD



DESCRIPTION

- Wired conference system with multiple functions including recording, voting and video tracking.

FEATURES

- Each desk has its own built-in 3W loudspeaker and headphone socket for listening.
- The CS-041C "President" console has a "TALK" button and a "PRIOR" button to mute all active consoles on the system.
- Up to 8 "President" consoles can be connected to a system.
- The CS-042D "Delegate" console has a "TALK" button and is at the same priority level as the other participants.
- All lecterns are fitted with a semi-rigid, thin electret microphone with a red light ring that lights up when the microphone is in use. The flexible microphone uses a 4-pin CB connector, making it easy to connect and disconnect.
- Modes AUTO/FIFO sélectionnables.
- The microphone can pick up sound up to 30 cm away.
- Volume control via potentiometer.
- Digital display showing the console number.
- Good sound quality over long-distance transmission.
- Quick and easy to install thanks to the connection cables supplied (1.3 ml with the microphone stands + 10 ml with the control unit).

- 5 Action buttons for the voting function
- DIN 8-pin input and output sockets.
- Dimensions (W x D x H) :
 - Panels: 125 x 165 x 65 mm - Weight: 0.8 Kg
 - Flexible microphone: W 410 x Ø 30 mm, windscreen included

MODEL DESIGNATIONS

- Chairman's micro desk CS-041C
(code 02617) •
- "Delegate" micro desk CS-042D
(code 02618)



NEW

ČENTRALŮNĚT CS-240



MICROPHONE WITH
INTEGRATED SPEAKERS



VOTE



VIDEO
TRACKING



RECORD



FEATURES

- The CS-240 preamplifier control unit can accept up to 90 microphones (30 microphones on each LINK circuit) 4 DIN 8-pin ports for lecterns up to 100 m long
- LCD screen
- 1 MIC/LINE XLR input
- 1 AUX input (RCA)
- 1 AUX output (RCA)
- 1 AUX output (XLR)
- VIDEO inputs and outputs
- Integrated DSP module to prevent saturation
- Power supply: AC 100-240V / 240 V, 50/60 Hz
- Supplied with 1 x 10 m cable for connection to the first console circuit
- Dimensions: 480 x 360 x 85 mm (Integrated brackets)
- Weight : 5 Kg



MODEL DESIGNATION

Amplified control unit CS-240
(code 02616)

MICROPHONES
ET CONFÉRENCES